



EQUIPOS PARA POLVO Y LODO

HUSQVARNA S 26

Art.no: 967 66 39 01


S 26 is a powerful single-phase HEPA dust extractor to match the grinding machines Husqvarna PG 280, PG 450 and early entry saw Soff-Cut 150. It also matches small scarifiers and shot blasters as well as handheld power tools. This professional dust extractor is suitable for building, grinding, plaster and concrete dust. Equipped with two tested and certified HEPA H13 filters. Features include Jet Pulse pre-filter cleaning, hour counter and vacuum meter for filter control. The non-marking wheels are puncture free and lock at the front. The Longopac® bag hose system ensures simple, dust-free bag changes.

FEATURES



Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.



Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



Easy to transport

The welded frame enables easy transportation by resting the machine on the frame.

TECHNICAL DATA HUSQVARNA S 26

Art.no: 967 66 39 01

HUSQVARNA S 26

MOTOR

Diámetro máximo de brocas, manual	2.4 kW
Fases	1 ph
Voltaje	110-120 V
Corriente nominal, A	20 A
Ciclo de fase de corriente	50-60 Hz
Aspiración máx.	240 mbar
Fuente de alimentación	Cable

DATOS DEL PRODUCTO

Air flow	438 m³/h
Área de superficie de filtración primaria	3 m²
HEPA Filters 99.99% at 0.3 microns	2

DIMENSIONES

Longitud del producto	756 mm
Ancho del producto	546 mm
Altura del producto	1,275 mm
Peso	47 kg
Longitud del embalaje	756 mm
Ancho del embalaje	546 mm
Altura del embalaje	1,275 mm
Peso bruto del artículo	63,420 g





PRESEPARADORES
C/3000

Fuente de alimentación:

Manual

Capacidad del tanque de mezcla:

37 l

Peso:

27 kg



PULIDORAS PLANETARIAS
PG 450 II

Potencia (Clasificación del fabricante del motor.):

1.54 kW

Fases:

1 ph

Anchura de pulido:

450 mm

Peso:

109 kg



CORTADORAS SOFF-CUT
SOFF-CUT 150

Profundidad de corte máx.:

38 / 38.1 mm

Diámetro disco, máx.:

165 mm

Potencia (Clasificación del fabricante del motor.):

3.6 / 4 kW